

Trailer Mounted Air Foam Unit

1350/2500

specifications

trailer	Lufkin or Great Dane 45' x 102" drop-deck trailer with hydraulic leveling legs, total weight is approximately 58,000 lbs
air compressor	Sullair two-stage rotary screw, oil-flooded, high pressure air end, providing up to 1,350 SCFM and 500 PSIG
air compressor engine	Caterpillar C-18: 6-cylinder, 4-cycle, 18-liter, EPA Tier III electronically controlled diesel engine rated at 700HP at 1,800 RPM, equipped with a spark arresting muffler Detroit Series 60: 6-cylinder, 4-cycle, 14-liter, EPA Tier II electronically controlled diesel engine rated at 665HP at 2,100 RPM, equipped with a spark arresting muffler
air booster	Ariel two-stage, double acting, air-cooled, high pressure reciprocating booster, inlet capacity of up to 1,350 SCFM at 2,500 PSIG
air booster engine	Caterpillar C-11: 6-cylinder, 4-cycle, 11-liter, EPA Tier III electronically controlled diesel engine rated at 350HP at 1,800 RPM, equipped with a spark arresting muffler Detroit Series 50: 6-cylinder, 4-cycle, 8.5-liter, EPA Tier II electronically controlled diesel engine rated at 315HP at 1,800 RPM, equipped with a spark arresting muffler
cooling system	designed to provide engines with adequate cooling up to 115° ambient temperature
mist pump	Kerr 3300 triplex pump, 3" stroke, 1¾" plungers, up to 50GPM at 2,500 PSIG
mist pump engine	Caterpillar C-4.4: 4-cylinder, 4-cycle, 4.4-liter, EPA Tier III electronically controlled diesel engine rated at 127HP at 2,200 RPM, equipped with a spark arresting muffler Detroit D704: 4-cylinder, 4-cycle, EPA Tier II mechanically controlled diesel engine rated at 87HP at 2,200 RPM, equipped with a spark arresting muffler
chemical injection pump	(2) Texsteam chemical injection pumps for precise control of corrosion inhibitor, foamer, or special chemical mixes
water tank	(2) 17 barrel, rectangular, open-top tank, valve configuration for 17 barrel or 34 barrel operation
fuel tank	(1) 1,500 gallon, rectangular, closed-top fuel tank providing up to 24 hours of operation without the need to refuel
manifold	2" Schedule-80 manifold with 1" orifice with blown down vent lines, bypass and discharge check valves

Key Energy Services
1301 McKinney St. Suite 1800
Houston, TX 77010
713.651.4300

keyenergy.com

1.14.KES3548 © 2014 Key Energy Services

