

Rig #104 “The Moccasin”

24-hour keyway workover barge

Description

130' x 40'8" x 6'8",

Keyway length 20' width 8' Drafts 2'

Barge # CB 22 3 Spuds, Clear Height above the barge – 10'



Specifications

Rig and Drawworks:	IDECO Hydrair H-35 model 308 “Rambler” SN #629 Single Drum, Trailer mounted back in unit
Engines:	Detroit Diesel Series 60 (475 HP), Allison 5860 transmission
Derrick:	95' / 212,000 telescoping Derrick Note: With 1 inch drill line the maximum hook load is 168,000 lbs on 6 lines and 112,000 lbs on 4 lines
Brakes:	35" x 10" Forged Steel with Water Splash cooling
Mud System:	Gardner Denver PAH Triplex Pump with 4-1/2' Lines Powered by GM 8V-71 diesel engine 180 Barrel Mud Tank (active tank), 180 Barrel holding tank Centrifugal pump powered by Detroit 471 Diesel Engine with Hopper Skidded
Generator:	200 KW Aggreko
Traveling Equipment:	McKissick 100 ton Traveling Block 2 3/8 and 2 7/8 elevators Complete set of rod tools (if needed)
Tubing Tongs:	Foster Type 58-93R
Air Slips:	Cavins Type C for 2-3/8, 2-7/8
BOP:	Hydril Century 7-1/16" dual 5000 psi, hydraulically operated
Lagniappe:	Sub-structured working platform Pusher House Dog House Diesel Tank 750 Gallons 1000 Gallon Fresh water Tank Circulating Manifold